

Product Description:  
UEGZ009  
WINEBERRY

MATERIAL SAFETY DATA SHEET

SECTION 1: MANUFACTURER IDENTIFICATION

MANUFACTURED BY:  
Custom-Pak Products Inc.  
N118 W18981 Bunsen Drive  
Germantown, WI 53022

FORMULA # 37L001N6  
Chemtrec 24-hour Emergency Phone: (800) 424-9300  
Chemtrec Foreign Emergency Phone: (703) 527-3887  
Product Information Phone Number: (262) 251-6180

DATE MSDS PRINTED & REVIEWED: 10/13/11  
LAST FORMULA REVISION DATE: 09/19/11

MANUFACTURED FOR: (C2718)  
FRONTLINE BLDG. PRODUCTS  
GREEN BAY, WI 54311

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

| #  | COMPONENT               | CAS#      | % by WT. | SARA 313 | LISTED CARCINOGEN BY: |      |      |
|----|-------------------------|-----------|----------|----------|-----------------------|------|------|
|    |                         |           |          | LISTED   | NTP                   | IARC | OSHA |
| 1  | ACETONE                 | 67-64-1   | 30-36    | N        | N                     | N    | N    |
| 2  | ETHYL ACETATE           | 141-78-6  | 15-21    | N        | N                     | N    | N    |
| 3  | PROPANE                 | 74-98-6   | 15-21    | N        | N                     | N    | N    |
| 4  | N-BUTANE                | 106-97-8  | 5-8      | N        | N                     | N    | N    |
| 5  | N-BUTYL ACETATE         | 123-86-4  | 3-5      | N        | N                     | N    | N    |
| 6  | ISOBUTYL ACETATE        | 110-19-0  | 3-5      | N        | N                     | N    | N    |
| 7  | CELLULOSE NITRATE       | 9004-70-0 | 1-3      | N        | N                     | N    | N    |
| 8  | ETHYL ESTER             | 763-69-9  | 1-3      | N        | N                     | N    | N    |
| 9  | ISOPROPYL ALCOHOL       | 67-63-0   | 1-3      | N        | N                     | N    | N    |
| 10 | ETHYL ALCOHOL (ETHANOL) | 64-17-5   | 1-3      | N        | N                     | N    | N    |

SECTION 3: HAZARDS IDENTIFICATION

Emergency Overview: DANGER! Extremely Flammable. Contents Under Pressure.

APPEARANCE/ODOR: Liquid Spray Mist / Solvent Odor

POTENTIAL HEALTH EFFECTS: See Section 11 for more information.

LIKELY ROUTES OF EXPOSURE: Eye contact, skin contact, ingestion, and inhalation  
EYE: Contact may cause redness, irritation, tearing, and blurred vision  
SKIN: Contact may dry skin causing cracks and irritation  
INGESTION: May be harmful if swallowed  
INHALATION: Exposure to high concentrations of vapors may cause drowsiness, breathing difficulty, respiratory irritation, or headaches. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Product Description:  
UEGZ009  
WINEBERRY

MATERIAL SAFETY DATA SHEET

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

Asthma and other respiratory ailments.

TARGET ORGANS: Kidney Liver Lung Brain

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

SECTION 4: FIRST AID MEASURES

EYE CONTACT: Immediately flush eyes with water for at least 15 minutes. If irritation develops get medical attention.  
SKIN CONTACT: Remove contaminated clothing and wash before reuse. Wash skin with soap and water. Get medical attention if irritation develops.  
INHALATION: Move to fresh air. Contact emergency medical support if breathing stops or is irregular.  
INGESTION: Do NOT induce vomiting. Get medical attention immediately.

SECTION 5: FIRE FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: CO2 (Carbon Dioxide), dry chemical, or water fog.  
UNSUITABLE EXTINGUISHING MEDIA: Water spray may be unsuitable. However, if water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible explosion when exposed to extreme heat.  
PRODUCTS OF COMBUSTION: These products are carbon oxides (CO,CO2).  
PROTECTION OF FIREFIGHTERS: Full protective equipment including self-contained breathing apparatus should be used.

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: Use personal protection recommended in Section 8.  
ENVIRONMENTAL PRECAUTIONS: None known.

Product Description:  
UEGZ009  
WINEBERRY

MATERIAL SAFETY DATA SHEET

METHODS OF CONTAINMENT: Absorb spilled liquid in suitable material.  
METHODS OF CLEAN-UP: Use spark-proof tools to sweep or scrape up and containerize.  
OTHER INFORMATION: Ventilate the area.

SECTION 7: HANDLING AND STORAGE

HANDLING:

Vapors may ignite explosively. Prevent buildup of vapors; use with adequate ventilation. Keep from sparks, heat, flame or other heat sources. Do not smoke. Turn off pilot lights, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Do not puncture or incinerate (burn) container.

STORAGE:

Store in dry, well-ventilated area and in accordance with federal, state, and local regulations. Do not expose to heat or store at temperatures above 120 F (48 C). Storage conditions should comply with NFPA 30B and OSHA 1910.106. If storing in cold temperatures, allow product to warm to room temperature before use.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE GUIDELINES

| #  | COMPONENT               | ACGIH TLV-STEL | ACGIH TLV-TWA | OSHA PEL-TWA |
|----|-------------------------|----------------|---------------|--------------|
| 1  | ACETONE                 | 750 ppm        | 500 ppm       | 1000 ppm     |
| 2  | ETHYL ACETATE           | N/E            | 400 ppm       | 400 ppm      |
| 3  | PROPANE                 | 1800 ppm       | 2500 ppm      | 1000 ppm     |
| 4  | N-BUTANE                | N/E            | 800 ppm       | 800 ppm      |
| 5  | N-BUTYL ACETATE         | 200 ppm        | 150 ppm       | 150 ppm      |
| 6  | ISOBUTYL ACETATE        | N/E            | 150 ppm       | 150 ppm      |
| 7  | CELLULOSE NITRATE       | N/A            |               | N/A          |
| 8  | ETHYL ESTER             | 100 ppm        | 50 ppm        | N/E          |
| 9  | ISOPROPYL ALCOHOL       | 400 ppm        | 200 ppm       | 400 ppm      |
| 10 | ETHYL ALCOHOL (ETHANOL) | N/E            | 1000 ppm      | 1000 ppm     |

ENGINEERING CONTROLS: Not generally required if product is applied in small quantities. If product is applied in larger quantities, provide ventilation to keep air contamination below OSHA permissible exposure limits and ACGIH TLV exposure levels.

EYE/FACE PROTECTION: Wear safety glasses with side shields. Have eye wash facilities immediately available.

SKIN PROTECTION: Chemical resistant gloves if contact is likely.

RESPIRATORY PROTECTION: Use NIOSH-approved air-purifying respirator with organic cartridge or canister if exposure cannot be controlled within applicable limits with ventilation.

GENERAL HYGIENE CONSIDERATIONS: Wash thoroughly after handling.

Product Description:  
UEGZ009  
WINEBERRY

MATERIAL SAFETY DATA SHEET

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Color: see product description  
Odor: Solvent Odor  
Physical State: Aerosol - Pressurized Liquid  
Freezing Point: Not Established (mixture)  
Boiling Range: <-18 C to 177 C (<0 F to 350 F)  
Flash Point: <-18 C (<0 F)  
Evaporation Rate: Faster than ether  
Upper Flammability Limit: Not Established (mixture)  
Lower Flammability Limit: Not Established (mixture)  
Vapor Pressure: Approximately 50 psig @ 10 C (70 F)  
Specific Gravity: 0.794 @15 C (60 F)  
Solubility (water): Negligible  
Percent Volatile, wt. %: 85.07  
VOC Percent (CA): 55.07  
MIR Number (CA): 0.607  
Coating Category (CA): EXACT-MATCH FINISH INDUSTRIAL

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable under normal conditions.

CONDITIONS TO AVOID: Keep away from heat, sparks, and flames.

INCOMPATIBLE MATERIALS: Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: by fire - Carbon Dioxide and Carbon Monoxide

POSSIBILITY OF HAZARDOUS REACTIONS: Will not occur.

Product Description:  
UEGZ009  
WINEBERRY

## MATERIAL SAFETY DATA SHEET

## SECTION 11: TOXICOLOGICAL INFORMATION

| #  | COMPONENT               | LD50 Oral   | LD50 Dermal    |
|----|-------------------------|-------------|----------------|
| 1  | ACETONE                 | 1000 mg/kg  | 2400 mg/kg     |
| 2  | ETHYL ACETATE           | 5620 mg/kg  | 20 ml/kg mg/kg |
| 3  | PROPANE                 | 1000 mg/kg  | 1800 mg/kg     |
| 4  | N-BUTANE                | N/E         | N/E            |
| 5  | N-BUTYL ACETATE         | 10768 mg/kg | 17601 mg/kg    |
| 6  | ISOBUTYL ACETATE        | 13400 mg/kg | 17400 mg/kg    |
| 7  | CELLULOSE NITRATE       | 5000 mg/kg  | 5000 mg/kg     |
| 8  | ETHYL ESTER             | 5000 mg/kg  | 10000 mg/kg    |
| 9  | ISOPROPYL ALCOHOL       | 4700 mg/kg  | 13000 mg/kg    |
| 10 | ETHYL ALCOHOL (ETHANOL) | N/E         | N/E            |

See section 3 for other acute effect information.

CHRONIC EFFECTS: Prolonged over-exposure to solvent ingredients in Section 2 may cause adverse effects to the liver, urinary, cardiovascular and reproductive systems. Reports have associated the repeated and prolonged occupational OVER-EXPOSURE to solvents with brain and nervous system damage. The deliberate misuse by concentrating and inhaling the vapors may be harmful or fatal.

CARCINOGENICITY: See Section 2 for additional information.

## SECTION 12: ECOLOGICAL INFORMATION

No data available.

## SECTION 13: DISPOSAL CONSIDERATIONS

Do not puncture, incinerate or place container in trash compactor. Dispose of product in accordance with Federal, State, and Local regulations. Empty containers are 95% steel; recycle where allowed.

Product Description:  
UEGZ009  
WINEBERRY

MATERIAL SAFETY DATA SHEET

SECTION 14: TRANSPORTATION INFORMATION

US DOT (Ground)

Proper Shipping Name: Consumer Commodity  
Hazard Class: ORM-D

US DOT (Air)

Proper Shipping Name: Consumer Commodity  
Hazard Class: ORM-D-AIR

IATA/ICAO (International Air)

Proper Shipping Name: Aerosols, Flammable

ID no.: UN1950

Hazard Class: 2.1

Hazard Label: Flammable Gas

Packing Instruction: 203 (NOTE, must be shipped in proper U.N.-certified box!)

No component of this product is a listed Marine Pollutant (49 CFR 172,101,Appendix B).

SECTION 15: REGULATORY INFORMATION

International Chemical Inventory

TSCA: United States The components of this product are listed on the TSCA inventory.

DSL: Canada The components of this product are listed on the DSL inventory.

AICS: Australia The components of this product are listed on the AICS inventory.

Section 313 Toxic Chemicals

See section 2. Chemicals marked with a "Y" are subject to the  
SARA reporting requirements under 40 cfr 372.45(c)(5).

\*California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65)

This product contains chemicals known to the state of California to cause cancer  
and birth defects or other reproductive harm.

SECTION 16: OTHER INFORMATION

HMIS(National Paint & Coatings Association's Hazardous Material Identification System):

Health = 2 Flammability = 4 Physical Hazard = 1

NFPA 704(National Fire Protection Association's Hazard Identification ratings system):

Health = 2 Flammability = 4 Instability = 1

Hazard Scale: 0=minimal, 1=slight, 2=moderate, 3-serious, 4=severe

This MSDS is based on information believed to be reliable and accurate. Because of  
changing reporting requirements and other variables it is impossible to guarantee  
the accuracy of the information contained in this document. It is the responsi-  
bility of the user to determine proper personal protection based on the actual  
condition of use and to comply with all Federal, State and Local laws and regulations.